

# HPRT D21 D31

2" / 3" Thermal Label Printer



<b>Model</b>		<b>D21</b>
<b>Printing</b>	Print Method	Direct Thermal
	Resolution	203 dpi (8 dots/mm)
	Print Speed	Max. 60 mm/s
	Length	15 mm ~ 300 mm
<b>Interface</b>	Standard	USB Type B
	Option	Bluetooth 4.0(Factory installed)
<b>Programming Language</b>		TSPL
<b>Memory</b>	RAM	2 MB
	ROM	2 MB
<b>Media</b>	Type	Roll or Fanfold label, die cut or continuous direct thermal labels, Tag stock, Continuous Receipt Paper
	Diameter(Media Roll)	90 mm
	Thickness	0.003"(60μm) ~ 0.007"(180μm)
<b>Barcode</b>	Linear Barcodes	CODE39, CODE93, EAN-8, EAN-13, EAN-2, EAN-5, UPC-A, UPC-E
	2D Barcodes	QR code
<b>Sensors</b>	Gap Sensor	Transmissive(Fixed)
	Other	Paper Out Sensor, Head-Up Sensor, TPH temperature detection
<b>Power Adapter</b>	Input	AC 100V ~ 240V, 50/60Hz

Output DC 12V, 2A

**Physical Characteristics**

182.5×134×120.6 mm

**Empty weight**

0.805kg

**Options & Accessories**

Bluetooth 4.0, External Label Roll Holder

**Reliability**

TPH 50 km

**Software**

Driver Windows Vista/7/8/10

Windows Server 2008/Server

2012/Server 2016

**Agency Approvals**

CCC, FCC, CE

---