

BP02-II 2" Direct Thermal Printer



Bluetooth

USB



Model	BP02-II RUGTEK		
Print Specifications	Print Speed: 50mm/s, Resolution : 203 dpi, Print Method: Direct Thermal RAM: 20KB, Flash: 128KB, Color: Black		
Media Specifications	Paper Width : 48mm, Print Width : 48mm, Paper Thickness: 0.05-0.15mm, Roll Capacity: 40mm (Outer dia)		
Media Sensor	Continuous Receipt, Label Gap & Black Mark Sensor		
Display/Reminding	Single Color : Power Red, Indicator: Feed Blue Button: Power, Feed		
Interface	Bluetooth, Micro USB		
Command/ OS Support	ESC/POS, XP, Win7, Win8, Win10, IOS, Android, Linux, MacOS Multi Language Support		
Power	Adapter: 5V/3A Battery Capacity: 3.7V, 1600MA		
Dimension(LxWxH)/ Weight	135(W)*1205(D)*78(H) / 0.455kg		
Environment Parameters	Temperature : -20°C	Storage:70°C	Working : 10°C—50°C
	Humidity Storage : 5%	Storage:95%	Working : 20%—85%
Other Accessories Supplied	MCBF - 5 million line, P H Life : 50 KM, USB Adapter Charger		

Solutions

