

# Product Comparison



**TE210**

## Hardware Specifications

Resolution 203 dpi (8 dots/mm)

<b>Print Method</b>	Direct thermal/Thermal transfer
<b>Display</b>	LED with buttons
<b>Hardwire Connectivity</b>	Ethernet Serial RS-232 USB USB Host
<b>Wireless Connectivity</b>	Bluetooth Wi-Fi
<b>Enterprise Printer Management</b>	TSC Console
<b>Type</b>	Desktop
<b>Max. Print Speed</b>	6 ips (152 mm/s)
<b>Max. Print Width</b>	4.25" (108 mm)
<b>Max. Print Length</b>	1,000" (24,400 mm)
<b>RAM</b>	64 MB SDRAM

<b>Flash</b>	128 MB
<b>Optional Cutter</b>	Guillotine cutter (full cut and partial cut)

## Media Specifications

<b>Internal Label Capacity</b>	5" (127 mm) OD
<b>Max. Media Width</b>	0.8" - 4.4" (20 - 112 mm)
<b>Ribbon &amp; Media Type</b>	Continuous; Die-Cut; Black Mark; Fan-Fold; Notched (Outside Wound)
<b>Max. Ribbon Length</b>	300 Meters
<b>Max. Ribbon Width</b>	1.6" - 4.3" (40 - 110 mm)
<b>Media Core Diameter</b>	1.0" - 1.5" (25.4 - 38 mm)
<b>Construction</b>	ABS plastic
<b>Programming Languages</b>	TSPL-EZD

[Cookie Settings](#)